

EF4502

LOW VOC Waterborne Two Pack Pigmented Primer

DESCRIPTION & USES This two component, waterborne primer is part of a coating system that revolutionises the wood coating industry by ticking all the boxes. EF4502 is LOW VOC meaning it is suitable for use in sensitive environments or projects with restrictions on emissions. Furthermore this primer delivers very good build and is efficient in production due to its very fast curing and excellent sanding properties.

Recommended Application:

For use under topcoat EH4120. Furniture, joinery, shopfitting, wardrobe and kitchen doors, commercial interiors.

DRY FILM PROPERTIES

Colour: White

Gloss: N/A

WET PROPERTIES

Solid content: Approx 56%

Viscosity in drum: 70 seconds Ford Cup 4 @ 20°C

Shelf life: 6 Months in sealed containers

Frost Sensitive: Yes. Do not store or use in temps below 5°C. Stir well before use

VOC Content: 74.10 g/L mixed with EV4345 hardener (from analysis)

APPLICATION

Method: Spraying

Mixing Ratio: EF4502 **20** parts to **1** part EV4345 HARDENER

IMPORTANT: Ensure hardener is mixed in by mechanical stir for 5 minutes

Thinning: Dilute with water if necessary

Pot Life: Approx 4 hours

Drying: Sanding: 4-6 hours at 20°C or 90 mins at 50°C

Application weight: 100 - 120 g/m²

NOTES

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974

NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299

VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389

QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au

Web www.22croma.com.au