

**GX4741-10%**  
**NATURA PARQUET/FLOORING OIL FOR TIMBER**

**DESCRIPTION & USES:**

GX4741-10% is a combination of natural vegetable based oils specially blended with high quality urethane oils for the coating of timber Parquet and Flooring. This specifically formulated oil product has excellent water-repellent properties and is very resistance to foot traffic. Also has excellent elasticity and durability.

For use on parquet, flooring, furniture and all timber flooring that is subject to high foot traffic as GX4741-10% has very good hardness and abrasion resistance.

**DRY FILM PROPERTIES:**

Colour: Amber  
Gloss: 10% Matt

**WET PROPERTIES:**

Solid Content (%): Approximately 52 ± 2  
Specific gravity (kg/l): 0.930 ± 0.030  
Viscosity in Drum: Approximately 150 ± 5 seconds Din Cup 4 at 20°C  
Shelf Life: 15 months in sealed containers

**TECHNICAL INFORMATION:**

Method: Brush, Spray, Roller and Wiping  
Mixing Ratio: 20% to 30%  
Thinning: Dilute with thinner BT4210 up to 30%  
Application: 2-3 coats  
Dry for overcoating: 12-16 hours at 20°C  
Dry for sanding: 16 hours at 20°C.  
Touch dry: 4-6 hours at 20°C  
Stacking: 48 hours at 20°C

**APPLICATION:**

**ON NEW WOOD:** apply a light coat by brush, spray, roll or wipe on the sanded bare wood (using 180 grit sandpaper). Then, after a few minutes wipe with a dry cloth to **ensure even absorption**. Take care not to apply a too heavy coat. Wait one (1) day before applying a second coat. Then after another day apply third coat.

**ON PREVIOUSLY COATED WOOD:** before applying the product, remove the old coating by sanding with a 180 grit sandpaper. Then, proceed as with new wood.

**ATTENTION:** cloths soaked with GX4741-10% Natura Parquet may be subject to spontaneous combustion. It is highly recommended that the cloths be soaked in water before being disposed of.

**Special Notes** \*Do not use on rainy days or too hot weather. \*Ensure timber is clean and dry prior to application.

**FOR INDUSTRIAL USE ONLY** Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

**AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS**

<b>WA:</b> TWENTY TWO SERVICES P/L	<b>Tel</b> (08) 9206 0220	<b>Fax</b> (08) 9206 0974
<b>NSW:</b> CROMA COATINGS	<b>Tel</b> (02) 9533 9122	<b>Fax</b> (02) 9533 9299
<b>VIC:</b> CROMA COATINGS VICTORIA	<b>Tel</b> (03) 9768 2312	<b>Fax</b> (03) 9768 2389
<b>QLD:</b> CROMA COATINGS QUEENSLAND	<b>Tel</b> (07) 3386 1000	<b>Fax</b> (07) 3386 1003

**Email** info@22croma.com.au  
**Web** www.22croma.com.au