

Issue Date: June 16

TL4371

Polyurethane Clear Sealer

DESCRIPTION & USES	Polyurethane two-component clear sealer for use on veneer and solid timbers such as furniture, kitchens and doors (interior). Properties include: very good covering power and build, very good sandability, fast curing, easy application on vertical surfaces and an ideal sealer for use on chairs and wall panelling. TL4371 uses 'low yellowing' hardeners designed specifically to reduce the yellowing of the coating itself. For protection against colour change of the timber substrate a UV prohibitor* can be added to TL4371 before application.
Recommended	
Application:	For use under topcoats TM4060 & TC4259. Furniture, joinery, shop-fitting, wardrobe and kitchen and vanity doors/benchtops, commercial interiors.

DRY FILM PROPERTIES

Colour:	Clear
Gloss:	N/A

WET PROPERTIES

Solid content:	45% (approx)
Viscosity in drum:	30-36 seconds Ford Cup 4 @ 20°C (approx)
Shelf life:	12 Months in sealed containers

APPLICATION

Method:	Spraying conventional	
Mixing Ratio:	2 Parts TL4371 to 1 Part TV4271 hardener	
Thinning:	THIN4230 at 20%-30% of part A (Depending on type of equipment used) In hot conditions use THIN4444/THIN4000 or NT573 can be added	
Drying:	Sand to re-coat: 3-4 hours at 20°C or 70-80 minutes at 50°C Stacking: 4-5 hours at 20°C or 70-80 minutes at 50°C	
Pot Life:	3-4 hours	
Application weight:	140 - 180 g/m2	
NOTES	* UV Prohibitor should also be added to the topcoat (e.g. TM4060) For further details and information please contact us	

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA:	TWENTY TWO SERVICES P/L	Tel (08) 9206 0220	Fax (08) 9206 0974
NSW:	CROMA COATINGS	Tel (02) 9533 9122	Fax (02) 9533 9299
VIC:	CROMA COATINGS VICTORIA	Tel (03) 9768 2312	Fax (03) 9768 2389
QLD:	CROMA COATINGS QUEENSLAND	Tel (07) 3386 1000	Fax (07) 3386 1003

Email info@22croma.com.au Web www.22croma.com.au