SHERWIN-WILLIAMS.

Technical Data Sheet

Issue Date: July 16

TM4269

Polyurethane Clear Multicoat Topcoat

DESCRIPTION & USES Polyurethane two component transparent "Multicoat" topcoat for use on veneer and

solid timbers in producing furniture, kitchens, cabinet doors & frames. This extremely 'versatile' topcoat is suitable for horizontal and vertical application for interior and

exterior and yields a durable, protecive and silky smooth finish.

Recommended

Application: Furniture, kitchens, cabinet doors and frames for interiors & exterior.

DRY FILM PROPERTIES

Colour: Clear

Gloss: 10% Matt, 30% Satin

WET PROPERTIES

Solid content: 42% (approx)

Viscosity in drum: 27-33 seconds DIN 4 @ 20°C (approx)

Specific gravity: 0.97 kg/L (approx)

Shelf life: 12 months in sealed containers at 30°C max

APPLICATION

Method: Spraying conventional, curtain coater, airless

Mixing Ratio & Thinning:

Product	By Volume
TM4269	100 parts
TV4271 **	50 parts
THIN-PU Standard	10-20 parts
Or for Exterior Application use	50 parts
TV4282 Hardener instead of TV4271 **	
See special note	

In hot conditions NT573 Retarder can be added to slow drying

Thinner amounts depend on the equipment used

Application weight: 100-140 g/m2 per coat

Drying time: Dust free: 10 mins at 20°C

Touch dry: 30 mins at 20°C

Stacking: 5-6 hours at 20°C or 60-80 minutes at 50°C Sanding & Over-coating: 5-6 hours at 20°C or 60-80 minutes at 50°C

Pot Life: 3-4 hours at 20°C (approx)

SPECIAL NOTEWhen using TV4282 hardener for exterior application UV Prohibitor <u>must</u> be added to this product. The use of TV4282 will increase the gloss level of this product to approx 40%.

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

 WA:
 TWENTY TWO SERVICES P/L
 Tel (08) 9206 0220
 Fax (08) 9206 0974

 NSW:
 CROMA COATINGS
 Tel (02) 9533 9122
 Fax (02) 9533 9299

 VIC:
 CROMA COATINGS VICTORIA
 Tel (03) 9768 2312
 Fax (03) 9768 2389

 QLD:
 CROMA COATINGS QUEENSLAND
 Tel (07) 3386 1000
 Fax (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au