

SL4360

Acrylic Polyurethane Clear Sealer

DESCRIPTION & USES Acrylic Polyurethane two component NON-YELLOWING sanding sealer. This 'water white' product has excellent non-yellowing characteristics making it ideal for sealing light timbers/woods and man-made veneers. SL4360 has very good build, is fast curing and sands well.

Recommended Application: For use under topcoats SM4006 and SC4220. Furniture, joinery,shop-fitting, wardrobe and kitchen and vanity doors/benchtops, commercial interiors.

DRY FILM PROPERTIES

Colour: Clear

Gloss: N/A

WET PROPERTIES

Solid content: 34% (approx)

Viscosity in drum: 60-70 seconds Ford Cup 4 @ 20°C (approx)

Shelf life: 12 Months in sealed containers

APPLICATION

Method: Spraying conventional

Mixing Ratio: 5 parts SL4360 to 1 part SV4360 hardener

Thinning: THIN4230 at 30%-50% of part A
(Depending on the type of equipment used)
In hot conditions use THIN4000 or THIN4444

Drying: Sanding: 5-6 hours at 20°C or 60-70 minutes at 50°C
Stacking: 5-6 hours at 20°C or 60-70 minutes at 50°C

Pot Life: 3-4 hours

Application weight: 140 - 180 g/m²

NOTES

UV Prohibitor XT170 (PU) can be added before application for extra protection to the substrate from discoloration caused by UV/Sunlight.

For details & further information please contact us.

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974
NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299
VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389
QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au