

Issue Date: June 16

SM4006

Acrylic Polyurethane Clear Topcoat

DESCRIPTION & USES	Acrylic Polyurethane two component NON-YELLOWING clear that can be used to both seal and topcoat. This 'water white' product has excellent non-yellowing characteristics making it ideal for application on light timbers/woods, man-made veneers and for use in making and over-coating metallics/pearls. Furthermore this product provides protection to the substrate from colour change due to UV light exposure with UV prohibitors added in the manufacturing process. SM4006 provides good surface hardness, good moisture		
Recommended Application:	resistancy, very good smoothness to the touch and good covering power. For use over sealer SL4340 & SL4360. Furniture, joinery, shop-fitting, wardrobe and kitchen and vanity doors/benchtops, commercial interiors.		
DRY FILM PROPERTIES			
Colour:	Clear		
Gloss:	10%, 25%, 30%, 60% (For high gloss use SC4220)		
WET PROPERTIES			
Solid content:	23% (approx)		
Viscosity in drum:	28-34 seconds Ford Cup 4 @ 20°C (approx)		
Shelf life:	12 Months in sealed containers		
APPLICATION			
Method:	Spraying conventional		
Mixing Ratio:	5 parts SM4006 to 1 part SV4310 hardener		
	or		
	10 parts SM4006 to 1 part SV4360 hardener (higher build – subject to availability)		
Thinning:	THIN4444 or THIN4000 at 10%-30% of part A (Depending on the type of equipment used) In hot conditions NT573 can be added		
Drying:	Dry for stacking: 5-6 hours at 20°C or 80-90 minutes at 50°C		
Pot Life:	24 hours (approx)		
Application weight:	100 - 140 g/m2		
NOTES Additional UV Prohibitor XT170 (PU) can be added before application for extra prote to the substrate from discoloration caused by UV/Sunlight.			

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA:	TWENTY TWO SERVICES P/L	Tel (08) 9206 0220	Fax (08) 9206 0974
NSW:	CROMA COATINGS	Tel (02) 9533 9122	Fax (02) 9533 9299
VIC:	CROMA COATINGS VICTORIA	Tel (03) 9768 2312	Fax (03) 9768 2389
QLD:	CROMA COATINGS QUEENSLAND	Tel (07) 3386 1000	Fax (07) 3386 1003

Email info@22croma.com.au Web www.22croma.com.au