

NF156

Care E1 Precatalysed Clear Sanding Sealer

DESCRIPTION & USES

One component, transparent, precatylised sanding sealer based on low formaldehyde binders and low toxicity solvents, which reduces risk with usage. This sealer has very good solids for filling the grain, is fast drying and has very good sanding characteristics. NF156 is free from aromatic hydrocarbon solvents.

Recommended Application:

For use as a sealer under NM800 & NM86920. Furniture, joinery, shop-fitting, wardrobe doors. N.B Not recommended for use on wet areas (i.e kitchen benchtops , vanity tops etc)

DRY FILM PROPERTIES

Colour: Clear

Gloss: N/A

WET PROPERTIES

Solid content: 34% (approx)

Viscosity in drum: 55-65 seconds Ford Cup 4 @ 20°C

Shelf life: 12 months in sealed containers

APPLICATION

Method: Spraying conventional, curtain coating

Thinning: DT8900 or BECKER22 at up to 30%
(Depending on type of equipment used)
In hot/humid/rainy conditions NT573 can be added

Drying: Sand to re-coat: 1-2 hours at 20°C or 25-30 minutes at 70°C
Stacking: 10-12 hours at 20°C or 1-2 hours at 70°C

NOTES

Not recommend for use when sealing Beech and Tasmanian Blackwood

Contact us for further information

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974
NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299
VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389
QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au