

TH4401-TEX

Polyurethane Pigmented Textured Topcoat

DESCRIPTION & USES Polyurethane two-component 'textured' pigmented topcoat with very good surface hardness, excellent water resistance and good resistance to marking. This paint has excellent build and covering power making it one of the most efficient and cost effective finishes available. A pleasant texture effect is achieved chemically during the curing process ensuring the finish is not rough and makes cleaning simple.

Recommended Application:

As a textured topcoat for use over undercoat TF4321 & TF4361 or Polyester PF0313. Furniture, joinery, shop-fitting, wardrobe/kitchen/vanity doors, commercial interiors.

DRY FILM PROPERTIES

Colour: White, can be tinted to most colours

Gloss: Low sheen

WET PROPERTIES

Solid content: 70% (approx)

Viscosity in drum: 95 seconds Ford Cup 4 @ 20°C (approx)

Shelf life: 12 Months in sealed containers

APPLICATION

Method: Spraying conventional

Mixing Ratio: 2 parts TH4401-TEX to 1 part TV4271 hardener

Thinning: THIN4000 or THIN4444 at 25%-35% of part A
(Depending on type of equipment used)
In hot conditions NT573 can be added

Drying: 5-6 hours at 20°C or 70-90 minutes at 50°C

Pot life: 5-6 hours

Application weight: 100 - 140 g/m²

NOTES

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974
NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299
VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389
QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au