

# TL4570

## Clear Isolator Sealer

**DESCRIPTION & USES**    Transparent polyurethane basecoat designed to have excellent wetting properties and adhesion to resinous woods. This isolator has very good elasticity and its adhesion properties make it suitable to use under PL4234 clear wax polyester.

**Recommended Application:**    For use under **PL4234** wax polyester or **PL4331** polyester basecoat

**WET PROPERTIES**

**Solid content:**                    16% (approx)  
**Viscosity in drum:**            10 seconds FORD CUP 4 @ 20°C (approx)  
 Specific gravity:                  0.88 kg/L (approx)  
**Shelf life:**                        12 months in sealed containers

**APPLICATION**

**Method:**                            Spraying conventional  
**Mixing Ratio:**                    1 Part TL4570 to 1 Part TV4117 hardener  
**Thinning:**                         No thinning required  
**Drying:**                            Stacking: 12 hours at 20°C

***For use under PL4234/PL4331:** Leave TL4570 to dry 1-2 hrs before over coating with PL4234/PL4331.*

***Note:** Refer notes on TDS for PL4234/PL4331 in regards to drying times and if sanding of TL4570 is required before over-coating.*

**Pot Life:**                            16-20 hours  
**Application weight:**            60-100 g/m2

**NOTES**                              Refer TDS for **PL4234** and **PL4331**

**FOR INDUSTRIAL USE ONLY** Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

**AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS**

**WA:** TWENTY TWO SERVICES P/L                    **Tel** (08) 9206 0220 **Fax** (08) 9206 0974  
**NSW:** CROMA COATINGS                            **Tel** (02) 9533 9122 **Fax** (02) 9533 9299  
**VIC:** CROMA COATINGS VICTORIA                **Tel** (03) 9768 2312 **Fax** (03) 9768 2389  
**QLD:** CROMA COATINGS QUEENSLAND        **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

**Email** info@22croma.com.au  
**Web** www.22croma.com.au